

COMPACTS

Features

Standard Equipment

- Driveable at full height
- Variable front wheel hydraulic drive
- 90° steering (zero inside turning radius)
- Dual holding brakes
- Proportional controls for drive/lift w/joystick controller
- 3' (0.9m) roll out extension deck
- 24V DC power source
- Low voltage battery protection
- 23% Gradeability
- Solid rubber, non-marking tires
- Pothole protection
- 110V GFI AC outlet on platform
- Tilt alarm with drive/lift cutout
- All motion audible alarm
- Lanyard attachment points
- Operator horn
- Forklift pockets, lifting lugs / tie downs



Optional Equipment **

- Flashing light
- Shop airline to platform
- 800 watt AC inverter
- EE rating package
- Hinged railing system
- Spring loaded half height gate
- Spring loaded full height gate*

* not available with hinged railing system

** Standard lead times may be increased when optional equipment is added, consult factory

Specifications

Model	SJIII 3215	SJIII 3219
Work Height	21' (6.4 m)	25' (7.6 m)
Raised Plat. Height (nom)	15' (4.6 m)	19' (5.8 m)
Lowered Platform Height	34.5" (0.88 m)	39" (0.99 m)
O/A Width	32" (0.81 m)	32" (0.81 m)
O/A Length	70" (1.78 m)	70" (1.78 m)
Stowed Height (rails up)	74" (1.88 m)	78.5" (1.99 m)
Stowed Height (rails down)	OPT. (60.1", 1.53 m)	OPT. (64.5", 1.64 m)
% Gradeability	23	23
Platform Size (inside dimension)	26" x 64" (0.66 m x 1.63 m)	26" x 64" (0.66 m x 1.63 m)
Capacity* Lbs (kg)	600lbs(272kb)	550lbs(249kb)
Travel speed mph (km/h)	2 mph (3.2 km/h)	2 mph (3.2 km/h)
Lift time (sec)	23	25
Weight * Lbs (kg)	2,400 lbs (1,089 kg)	2580 lbs (1,170 kg)

* Capacities, and machine weights may differ when options are added

For illustrative purposes only. Subject to change without notice.