

CONVENTIONALS

Features

Standard Equipment

- Driveable at full height
- Variable rear wheel hydraulic drive
- Dual holding brakes
- Proportional controls for drive/lift w/joystick controller
- 3' (0.9m) roll out extension deck (32XX's, 68XX's)
- **NEW!** 4' (1.2m) roll out extension deck (46XX's)
- 24V DC power source
- Low voltage battery protection
- 25% Gradeability
- Solid rubber, non-marking tires (except 6826, 6832)
- Black, foam-filled tires (6826, 6832)
- Pothole protection (except 6826, 6832)
- 110V GFI AC outlet on platform
- Tilt alarm with drive/lift cutout
- All motion audible alarm
- Lanyard attachment points
- Operator horn
- Hinged railing system (except 3220, 4620)
- Forklift pockets, lifting lugs / tie downs



Optional Equipment **

- Flashing light
- 6' powered deck ext. 3220
- 6' powered deck ext. 4620, 4626
- 5' powered deck ext. 6826, 6832
- Shop airline to platform
- 800 watt AC inverter
- EE rating package
- Hinged railing system - 3220
- Hinged railing system - 4620
- Spring loaded half height gate
- Spring loaded full height gate*
- Non-marking, foam-filled tires (6826, 6832 only)
- Air operation package

*not available with hinged railing system on 3220, 3226

** Standard lead times may be increased when optional equipment is added, consult factory

Specifications

Model	3220	3226	4620	4626	4632	6826	6832
Work Height	26' (7.9 m)	32' (9.7 m)	26' (7.9 m)	32' (9.7 m)	38' (11.5 m)	32' (9.7 m)	38' (11.5 m)
Raised Plat. Height (nom)	20' (6.1 m)	26' (7.9 m)	20' (6.1 m)	26' (7.9 m)	32' (9.7 m)	26' (7.9 m)	32' (9.7 m)
Lowered Platform Height	38" (0.97 m)	45" (1.14 m)	38" (0.97 m)	45" (1.14 m)	48.5" (1.23 m)	50" (1.27 m)	55.5" (1.40 m)
O/A Width	32" (0.81 m)	32" (0.81 m)	46" (1.16 m)	46" (1.16 m)	46" (1.17 m)	68" (1.72 m)	68" (1.72 m)
O/A Length	91.5" (2.32 m)	91.5" (2.32 m)	91" (2.31 m)	91" (2.31 m)	91" (2.31 m)	99.5" (2.52 m)	99.5" (2.52 m)
Stowed Height (rails up)	77.5" (1.97 m)	84.7" (2.15 m)	77" (1.96 m)	84.5" (2.15 m)	88" (2.24 m)	93.5" (2.37 m)	99" (2.51 m)
Stowed Height (rails down)	OPT. (63.5", 1.61 m)	70.6" (1.79 m)	OPT.	70.5" (1.79 m)	74" (1.88 m)	78.5" (1.99 m)	84" (2.13 m)
% Gradeability	25	25	25	25	25	25	25
Platform Size (inside dimension)	28" x 84" (.71 x 2.13 m)	28" x 84" (.71 x 2.13 m)	42" x 84" (1.07 x 2.13 m)	42" x 84" (1.07 x 2.13 m)	42" x 84" (1.07 x 2.13 m)	57" x 84" (1.45 x 2.13 m)	57" x 84" (1.45 x 2.13 m)
Capacity* Lbs (kg)	900 lb (408 kg)	500 lb (227 kg)	1,300 lb (590 kg)	1,000 lb (454 kg)	700 lb (318 kg)	1,200 lb (544 kg)	850 lb (386 kg)
Travel speed mph (km/h)	2 mph (3.2 km/h)	2 mph (3.2 km/h)	2 mph (3.2 km/h)	2 mph (3.2 km/h)	2 mph (3.2 km/h)	2 mph (3.2 km/h)	2 mph (3.2 km/h)
Lift time (sec)	33	56	32	55	58	65	60
Weight * Lbs (kg)	3,510 lb (1,592 kg)	4,135 lb (1,876 kg)	4,100 lb (1,860 kg)	4,700 lb (2,132 kg)	5,100 lb (2,313 kg)	5,380 lb (2,440 kg)	5,680 lb (2,576 kg)

* Capacities, and machine weights may differ when options are added

For illustrative purposes only. Subject to change without notice.