

SJIII SERIES

Compacts

		3215	3219
Dimensional Specifications			
Work Height	ft	21	25
Raised Platform Height	ft	15	19
Lowered Platform Height	in	34.5	39
O/A Width	in	32	32
O/A Length	in	70	70
Stowed Height (rails up)	in	74	78.5
Stowed Height (rails down)	in	OPT (60.1)	OPT (64.5)
Platform Width (inside dimension)	in	26	26
Platform Length (inside dimension)	in	64	64
Deck Extension		3' roll out	3' roll out
Ground Clearance (stowed)	in	2.375	2.375
Ground Clearance (raised)	in	0.7	0.7
Wheelbase	in	55	55
Technical Specifications			
Weight	lbs	2400	2580
Gradeability	%	23	23
Turning Radius (inside)	in	0	0
Turning Radius (outside)	in	66	66
Lift Time (with rated load)	sec	23	25
Lower Time (with rated load)	sec	24	32
Drive Speed (stowed)	mph	2	2
Drive Speed (raised)	mph	0.7	0.7
Maximum Drive Height		Full height	Full height
Capacity (overall)	lbs	600	550
Distributed Capacity (main platform)	lbs	350	300
Distributed Capacity (extension deck)	lbs	250	250
Floor Load Rating (with rated load)	psi	110	110
Tire type		Solid, N/M	Solid, N/M
Tire size		12 x 4 x 8	12 x 4 x 8

Standard Features

- ✓ Variable front wheel hydraulic drive
- ✓ 90° steering (zero inside turn radius)
- ✓ Dual parking brakes
- ✓ Proportional controls for drive/lift w/joystick controller
- ✓ 24V DC power source
- ✓ Low voltage battery protection
- ✓ Pothole protection
- ✓ 110V GFI AC outlet on platform
- ✓ Tilt alarm with drive/lift cutout
- ✓ All motion alarm
- ✓ Lanyard attachment points
- ✓ Operator horn
- ✓ Mid-rail chain entrance
- ✓ Forklift pockets, lifting lugs / tie downs
- ✓ Freewheeling valve
- ✓ Positive traction
- ✓ Hourmeter
- ✓ Color coded and numbered wiring system
- ✓ Hydraulic oil level and temperature indicators
- ✓ Swing out trays for easy access
- ✓ Battery charger
- ✓ Base controls
- ✓ Comprehensive Parts/Operating and Service manual